

Features

- Low forward voltage drop
- Soft recovery
- Hermetic metal cases with ceramic insulators

I_{F(AV)} **880 A**
V_{RRM} **1100~2000V**
t_{rr} **3.0μs**

Typical Applications

- Inverters and choppers
- Motor control
- Snubber and free-wheeling diodes



SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Double side cooled,	150			880	A
V _{RRM}	Repetitive peak reverse voltage	t _p =10ms	150	1100		2000	V
I _{RRM}	Repetitive peak current	at V _{RRM}	150			50	mA
I _{FSM}	Surge forward current	10ms half sine wave V _R =0.6V _{RRM}	150			12	kA
I ² t	I ² t for fusing coordination					720	A ² s*10 ³
V _{FO}	Threshold voltage		150			1.51	V
r _F	Forward slope resistance					0.37	mΩ
V _{FM}	Peak forward voltage	I _{TM} =2400A, F=15kN	25			2.8	V
I _{rm}	Reverse recovery current	I _{TM} =1000A, t _p =2000μs, -di/dt=60A/μs, V _R =50V	150			76	A
t _{rr}	Reverse recovery time					3.0	μs
Q _{rr}	Recovery charge					114	130
R _{th(j-c)}	Thermal resistance Junction to case	At 180° sine double side cooled Clamping force 15kN				0.035	°C /W
R _{th(c-h)}	Thermal resistance case to heat sink					0.008	
F _m	Mounting force					10	20
T _{stg}	Stored temperature					-40	160
W _t	Weight					250	g
Outline	ZT33CT						

Outline

