

Features

- Low forward voltage drop
- Soft recovery
- Hermetic metal cases with ceramic insulators

I_{F(AV)} **1876A**
V_{RRM} **2100~3000V**
t_{rr} **10.0μs**

Typical Applications

- Inverters and choppers
- Motor control
- Snubber and free-wheeling diodes



SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Double side cooled,	150			1876	A
V _{RRM}	Repetitive peak reverse voltage	t _p =10ms	150	2100		3000	V
I _{RRM}	Repetitive peak current	at V _{RRM}	150			195	mA
I _{FSM}	Surge forward current	10ms half sine wave	150			25	kA
I ² t	I ² t for fusing coordination	V _R =0.6V _{RRM}				3125	A ² s*10 ³
V _{FO}	Threshold voltage		150			1.55	V
r _F	Forward slope resistance					0.29	mΩ
V _{FM}	Peak forward voltage	I _{TM} =3000A, F=35kN	25			3.20	V
I _{rm}	Reverse recovery current	I _{TM} =2000A, t _p =2000μs, -di/dt=60A/μs, V _R =50V			260		A
t _{rr}	Reverse recovery time		150		10		μs
Q _{rr}	Recovery charge				1300	1500	μC
R _{th(j-c)}	Thermal resistance Junction to case	At 180° sine double side cooled Clamping force 35kN				0.012	°C /W
R _{th(c-h)}	Thermal resistance case to heat sink					0.003	
F _m	Mounting force			30		40	kN
T _{stg}	Stored temperature			-40		160	°C
W _t	Weight					880	g
Outline	ZT60cT70						

Outline:

