

Features

- Low forward voltage drop
- High reverse voltage
- Hermetic metal cases with ceramic insulators

Typical Applications

- All purpose high power rectifier diodes
- High power resistance welding equipment
- Non-controllable and half-controllable rectifiers
- Controlled rectifiers

$I_{F(AV)}$

7230A

V_{RRM}

1100~2000 V

I_{FSM}

83 kA

I^2t

34445 $10^3 A^2S$



SYMBOL	CHARACTERISTIC	TEST CONDITIONS		T _j (°C)	VALUE			UNIT
					Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Double side cooled,	T _C =85°C	175			7230	A
V _{RRM}	Repetitive peak reverse voltage	tp=10ms		175	1100		2000	V
I _{RRM}	Repetitive peak current	at V _{RRM}		175			200	mA
I _{FSM}	Surge forward current	10ms half sine wave		175			83	kA
I ² t	I ² t for fusing coordination	V _R =0.6V _{RRM}					34445	A ² s*10 ³
V _{FO}	Threshold voltage			175			0.80	V
r _F	Forward slope resistance						0.055	mΩ
V _{FM}	Peak forward voltage	I _{FM} =5000A, F=70kN		25			2.0	V
Q _{rr}	Recovery charge	I _{FM} =2000A, tp=2000μs, di/dt=-20A/μs, V _R =50V		175		6000		μC
R _{th(j-c)}	Thermal resistance Junction to case	At 180° sine: double side cooled Clamping force 70kN					0.007	°C /W
R _{th(c-h)}	Thermal resistance case to heat sink						0.002	
F _m	Mounting force				63		84	kN
T _{stg}	Stored temperature				-40		175	°C
W _t	Weight					1390		g
Outline	ZT84cT							




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8

Outline:

